

14 MM SPIREX 320N / R30



Spiralled flexible sheaths 2311. It is lead-free (ROHS compliant) and it has a watertight system:

protection degree IP65 if used with fittings RAI-RAG-RAP and IP66 with fittings RK.

The colour is grey (RAL 7035).

Art. code:	GUS14G
Spirex	14mm
Classification	2311
Conduit colour	Grey - RAL 7035
External diameter	18,9 mm
Internal diameter	14 mm
Coil	30 m
Pallet	5400 m

Technical information

Conduit technical specification

Material	PVC
Compression resistance	320N (23°C, +/- 2°C) - Light
Resistance to impact	2J - Medium
Min. operating temperature	+5°C
Max. operating temperature	+60°C
Certifications	
Standard	EN 61386.1, EN 61386.23

Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
Compliant with Low Voltage Directive	LVD 2013/35/EU
Packed with 100% recyclable PE film	

Related products



25 mm Speed BK 750N / R100

Art. code: ICTAN25



20 mm Speed F 750N / R100

Art. code: ICTA20F



20 mm Speed 750N / R100

Art. code: ICTA20



40 mm Speed 750N / R50

Art. code: ICTA40



32 mm Speed F 750N / R50

Art. code: ICTA32F



16 mm Speed 750N / R100

Art. code: ICTA16