

20 MM / H07Z1-K 5G1,5 BGMNT / R100



Pre-wired pliable corrugated conduit with H07Z1-K energy cables. Save time: installation times are halved. Save money and workforce: one person can easily do the job alone.

Maximize safety: no risks of damaging the cables during pulling operations. Within the conduit, there is enough space left to add other cables after the installation. Thanks to the internal lubrication, in-pulling and out-pulling operations are very easy. Metrically marked. The conduit and the cables are LSZH (Low Smoke Zero Halogen), ideal for installations in buildings aimed at hosting high numbers of people, such as schools, hospitals, stations, museums, shopping malls, etc.

Art. code:

Classification	ICTA 34223
Conduit colour	Grey - RAL 7037
External diameter	20 mm
Cables number	5
Cables section	1,5 mm ²
Cable type	H07Z1-K
Cables colour	Blue - Grey - Brown - Black - Yellow/Green
Coil	100 m

H07Z1-K

5G1,5

Technical information

Environmental certificate

Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	Yes
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

Conduit technical specification

Material	Polypropylene
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	6J (IK08) - Heavy
Min. operating temperature	-5°C
Max. operating temperature	+90°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C

Certifications



Conduit properties

LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1; IEC 60754-2
Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22

Conduit properties

Self-recovering (of at least 90% of original diameter)	EN 61386.1, EN 61386.22
According to Low Voltage Directive	LVD 2014/35/EU
Packed with 100% recyclable PE film	■
HF - Halogen Free	EN 50642, DIN VDE V 0604-2-100
Anti-UV	EN 50618:2015-12

Cable Technical Specification

Type	H07Z1-K
Code	KH
Application	Energy
Number	5
Section	1,5 mm ²
Colour	Blue - Grey - Brown - Black - Yellow/Green
Outer Sheath	LSZH compound
Rated Voltage	450/750 V
Operating Temperature	-10°C/+70°C
C.P.R. Euroclass	Dca-s2,d2,a2

Certifications



