

## 20 MM / H07Z1-U 3G1,5 BNT / R100



Pre-wired pliable corrugated conduit with H07Z1-U energy cables. Save time: installation times are halved. Save money and workforce: one person can easily do the job alone.

Maximize safety: no risks of damaging the cables during pulling operations. Within the conduit, there is enough space left to add other cables after the installation. Thanks to the internal lubrication, in-pulling and out-pulling operations are very easy. Metrically marked. The conduit and the cables are LSZH (Low Smoke Zero Halogen), ideal for installations in buildings aimed at hosting high numbers of people, such as schools, hospitals, stations, museums, shopping malls, etc.

---

<b>Art. code:</b>	F2HC15BNT
<b>Classification</b>	ICTA 34223
<b>Conduit colour</b>	Blue - RAL 5017
<b>External diameter</b>	20 mm
<b>Cables number</b>	3
<b>Cables section</b>	1,5 mm <sup>2</sup>
<b>Cable type</b>	H07Z1-U
<b>Cables colour</b>	Blue - Black - Yellow/Green
<b>Coil</b>	100 m

## Technical information

### Environmental certificate

Environmental Product Declaration 

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	Yes
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

### Conduit technical specification

Material	Polypropylene
Compression resistance	750N (23°C, +/- 2°C) - Medium - (3)
Resistance to impact	6J (IK08) - Heavy - (4)
Min. operating temperature	-5°C - (2)
Max. operating temperature	+90°C - (2)
Bending resistance	Pliable - Self-recovering - (3)
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C

Certifications



### Conduit properties


LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1; IEC 60754-2
Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22

---

**Conduit properties**

Self-recovering (of at least 90% of original diameter) EN 61386.1, EN 61386.22

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE film 

---

**Cable Technical Specification**

Type H07Z1-U  
Code HC  
Application Energy  
Number 3  
Section 1,5 mm<sup>2</sup>  
Colour Blue - Black - Yellow/Green  
Outer Sheath LSZH compound  
Rated Voltage 450/750 V  
Operating Temperature -10°C/+70°C  
C.P.R. Euroclass Cca s1d1a1

Certifications



