


## 20 MM PVC LIGHT 320N / R50



Light class. Made in PVC. Colour: grey (RAL 7035).

---

<b>Art. code:</b>	IPS20
<b>xSpeed PVC LIGHT</b>	20 mm
<b>Classification</b>	22212
<b>Conduit colour</b>	Grey - RAL 7035
<b>External diameter</b>	20 mm
<b>Internal diameter</b>	14,1 mm
<b>Coil</b>	50 m
<b>Pallet</b>	4200 m

## Technical information

---


### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes*
Chased floor	No
False ceiling - Movable wall	Yes*
Prefab - Wood panels	Yes*

*\*Only for electrical installations that do not require HF/LSFOH conducts systems*

---

### Conduit technical specification

Material	PVC
Compression resistance	320N (23°C, +/-2°C) - Light
Resistance to impact	1J - Light
Min. operating temperature	-5°C
Max. operating temperature	+60°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

---

### Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

**Conduit properties**

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Packed with 100% recyclable PE

film



