# 25 MM PVC ICE -25 750N / R50



Very high resistance at low temperatures: -25°C. Made in PVC. Colour: grey (RAL 7037).

| | |
|---|---|
| **Art. code:** | ICE25 |
| **Classification** | 33412 |
| **Conduit colour** | Grey - RAL 7037 |
| **External diameter** | 25 mm |
| **Internal diameter** | 18,2 mm |
| **Coil** | 50 m |
| **Pallet** | 2800 m |

# Technical information

**Environmental certificate**

| | |
|---|---|
| Environmental Product Declaration | EPD® |

**Applications**

| | |
|---|---|
| Outdoor | No |
| Indoor | Yes |
| Exposed Installation | No* |
| Liquid screed and concrete | Yes** |
| Chased wall - Plasterboard | Yes** |
| Chased floor | Yes** |
| False ceiling - Movable wall | Yes** |
| Prefab - Wood panels | Yes** |
| - | **Check local regulations* |
| - | ***Only for electrical installations that do not require HF/LSF0H conducts systems* |

**Conduit technical specification**

| | |
|---|---|
| Material | PVC |
| Compression resistance | 750N (23°C, +/- 2°C) - Medium - (3) |
| Resistance to impact | 2J (IK08) - Medium - (3) |
| Min. operating temperature | -25°C - (4) |
| Max. operating temperature | +60°C - (1) |
| Bending resistance | Pliable - (2) |
| Insulation resistance | >100MΩ |
| Glow Wire Test (IEC EN 60695-2) | 960°C (IMQ) |
| Certifications | ÖVE |
| Standard | EN 61386.1, EN 61386.22, IK: EN 62262 |

| **Conduit properties** | |
|---|---|
| Fire resistance: non-flame propagating | EN 61386.1, EN 61386.22 |
| Conforme alla Direttiva Bassa Tensione | LVD 2014/35/EU |
| Pre-lubricated | ✓ |
| Packed with 100% recyclable PE film | ✓ |