

## 25 MM PVC ICE -25 F 750N / R50



Very high resistance at low temperatures: -25°C. Made in PVC. Colour: grey (RAL 7037).  
With wire.

---

<b>Art. code:</b>	ICE25F
<b>xSpeed PVC ICE -25</b>	25 mm
<b>Classification</b>	33412
<b>Conduit colour</b>	Grey - RAL 7037
<b>External diameter</b>	25 mm
<b>Internal diameter</b>	18,2 mm
<b>Coil</b>	50 m
<b>Pallet</b>	2800 m

## Technical information


---

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No*
Liquid screed and concrete	Yes**
Chased wall - Plasterboard	Yes**
Chased floor	Yes**
False ceiling - Movable wall	Yes**
Prefab - Wood panels	Yes**
-	<i>*Check local regulations</i>
-	<i>**Only for electrical installations that do not require HF/LSFOH conducts systems</i>

---

### Conduit technical specification

Material	PVC
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	2J (IK08) - Medium
Min. operating temperature	-25°C
Max. operating temperature	+60°C
Bending resistance	Pliable
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

---

### Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

**Conduit properties**

Compliant with Low Voltage Directive	LVD 2014/35/EU
Pre-lubricated	■
Packed with 100% recyclable PE film	■

