


## 25 MM PVC WT F 750N / R100



The PVC conduit with wire is ideal in standard installations that do not require the use of LSF0H materials; it is not suitable with liquid concrete and reinforced concrete. The conduit is made with ecological PVC and it is also internally lubricated. The colour of the conduit is white pearl (RAL 1013).

---

<b>Art. code:</b>	IPCX25F
<b>Classification</b>	33212
<b>Conduit colour</b>	White - RAL 1013
<b>External diameter</b>	25 mm
<b>Internal diameter</b>	18,2 mm
<b>Coil</b>	50 m
<b>Pallet</b>	1200 m

## Technical information

### Environmental certificate


Environmental Product Declaration 

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes*
Chased floor	Yes*
False ceiling - Movable wall	Yes*
Prefab - Wood panels	Yes*

- *\*Only for electrical installations that do not require HF/LSFOH conducts systems*

### Conduit technical specification

Material	PVC
Compression resistance	750N (23°C, +/- 2°C) - Medium - (3)
Resistance to impact	2J (IK07) - Medium - (3)
Min. operating temperature	-5°C - (2)
Max. operating temperature	+60°C - (1)
Bending resistance	Pliable - Self-recovering - (2)
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

---

**Conduit properties**

Fire resistance: non-flame  
propagating

EN 61386.1, EN 61386.22

Compliant with Low Voltage  
Directive

LVD 2014/35/EU

Pre-lubricated

✓

Packed with 100% recyclable PE  
film

✓

