

## 32 MM PVC BN 750N / R25



The PVC conduit is ideal in standard installations that do not require the use of LSF0H materials; it is not suitable with liquid concrete and reinforced concrete. The conduit is made with ecological PVC and it is also internally lubricated. The colour of the conduit is brown (RAL 8012).

---

<b>Art. code:</b>	IPCM32
<b>xSpeed PVC</b>	32 mm
<b>Classification</b>	33212
<b>Conduit colour</b>	Brown - RAL 8012
<b>External diameter</b>	32 mm
<b>Internal diameter</b>	24,2 mm
<b>Coil</b>	25 m
<b>Pallet</b>	900 m

## Technical information


---

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes*
Chased floor	Yes*
False ceiling - Movable wall	Yes*
Prefab - Wood panels	Yes*
-	<i>*Only for electrical installations that do not require HF/LSFOH conducts systems</i>

---

### Conduit technical specification

Material	PVC
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	2J (IK07) - Medium
Min. operating temperature	-5°C
Max. operating temperature	+60°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

---

### Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

**Conduit properties**

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Packed with 100% recyclable PE

film



