

32 MM SPEED HF BL 750N / R100



Self-recovering pliable conduit, totally free of micro-holes. Internal lubrication for diameter 16, 20 and 25 mm. It can be used with cement and concrete. Self-protected: it doesn't need concrete cover. Eco-friendly: Halogen Free according to the European standard EN 50642. Colour: blue (RAL 5017).

Art. code:	ICTAHFA32
Classification	ICTA 34223 - 33423
Conduit colour	Blue - RAL 5017
External diameter	32 mm
Internal diameter	24,2 mm
Coil	50 m
Pallet	1800 m
xSpeed HF	32 mm

Technical information

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	Yes
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

Conduit technical specification

ICTA	34223
Material	Polypropylene
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	6J (IK08) - Heavy
Min. operating temperature	-5°C
Max. operating temperature	+90°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	        
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

Conduit technical specification 2

ICTA	33423
Material	Polypropylene
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	6J (IK08) - Heavy

Conduit technical specification 2

Min. operating temperature	-5°C
Max. operating temperature	+90°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	960°C
Glow Wire Test (IEC EN 60695-2)	960°C

Certifications



Standard

EN 61386.1, EN 61386.22, IK: EN 62262

Conduit properties

LS - Low Smoke	IEC 61034-2
HF - Halogen Free	EN 50642, DIN VDE V 0604-2-100
OH - Zero Halogen	IEC 60754-1; IEC 60754-2
Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
Self-recovering (of at least 90% of original diameter)	EN 61386.1, EN 61386.22
According to Low Voltage Directive	LVD 2014/35/EU
Pre-lubricated	■
Packed with 100% recyclable PE film	■

Related products



32mm xSpeed HF UV R25

Art. code: ICTANUV3225RT24



40mm xSpeed HF UV R25

Art. code: ICTANUV4025RT20



50 mm Speed F 750N / R50

Art. code: ICTA50F50



50mm xSpeed HF UV R25

Art. code: ICTANUV5025RT8



40 mm Speed F 750N / R50

Art. code: ICTA40F



32 mm Speed F 750N / R50

Art. code: ICTA32F