

32 MM SUPERBLU VT 1000N / R100



The Pmflex SuperBlu conduit has high flexibility and very high compression resistance: 1000 N. The conduit is self-recovering and totally free of micro-holes, therefore it can be used with cement and concrete. Furthermore, it is also internally lubricated (diameters 16, 20, 25 mm), metrically marked (diameters 16, 20, 25 mm) and environmentally friendly (Low Smoke Flame retardant Zero Halogen). SuperBlu is the only SEV and IMQ certified conduit resistant to temperatures of -15°C and to shocks of 6 Joules. The color of the conduit is violet RAL 4008 (utility lines: TV/coaxial cables).

Art. code:	ICTAAMVI32
xSpeed SuperBlu	32 mm
Classification	34323
Conduit colour	Violet - RAL 4008
External diameter	32 mm
Internal diameter	24,2 mm
Coil	100 m
Pallet	1800 m

Technical information


Environmental certificate

Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	Yes
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

Conduit technical specification

Material	Polypropylene
Compression resistance	1000N (23°C, +/- 2°C) - Medium
Resistance to impact	6J (IK08) - Heavy
Min. operating temperature	-15°C
Max. operating temperature	+90°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

Conduit properties

LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1; IEC 60754-2

Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
Self-recovering (of at least 90% of original diameter)	EN 61386.1, EN 61386.22
Compliant with Low Voltage Directive	LVD 2014/35/EU
Pre-lubricated	■
Metrically marked	■
Packed with 100% recyclable PE film	■

