

## 40 MM XSPEED 750N / R50



Self-recovering pliable conduit, totally free of micro-holes. Internal lubrication for diameter 16, 20 and 25 mm. It can be used with cement and concrete. Self-protected: it doesn't need concrete cover. Eco-friendly: LSF0H (Low Smoke Flame retardant Zero Halogen). Colour: grey (RAL 7037).

---

<b>Art. code:</b>	ICTA40
<b>xSpeed</b>	40 mm
<b>Classification</b>	ICTA 34223 - 33423
<b>Conduit colour</b>	Grey - RAL 7037
<b>External diameter</b>	40 mm
<b>Internal diameter</b>	32,4 mm
<b>Coil</b>	50 m
<b>Pallet</b>	1400 m

## Technical information

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	Yes
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

### Conduit technical specification

Material	Polypropylene
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	6J (IK08) - Heavy
Min. operating temperature	-5°C
Max. operating temperature	+90°C
Bending resistance	Pliable - Self-recovering
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C

Certifications



Standard

EN 61386.1, EN 61386.22, IK: EN 62262

### Conduit properties

LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1; IEC 60754-2
Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22

**Conduit properties**

Self-recovering (of at least 90% of original diameter) EN 61386.1, EN 61386.22

Compliant with Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE film ■

