

## 50 MM PVC BK 750N / R25



The PVC conduit is ideal in standard installations that do not require the use of LSF0H materials; it is not suitable with liquid concrete and reinforced concrete. The conduit is made with ecological PVC and it is also internally lubricated. The colour of the conduit is black (RAL 9004).

---

<b>Art. code:</b>	IPCN50
<b>Conduit colour</b>	Black - RAL 9004
<b>External diameter</b>	50 mm
<b>Internal diameter</b>	41,2 mm
<b>Coil</b>	25 m
<b>Pallet</b>	800 m

## Technical information

### Environmental certificate


Environmental Product Declaration 

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes*
Chased floor	Yes*
False ceiling - Movable wall	Yes*
Prefab - Wood panels	Yes*

- *\*Only for electrical installations that do not require HF/LSFOH conducts systems*

### Conduit technical specification

Material	PVC
Compression resistance	750N (23°C, +/- 2°C) - Medium - (3)
Resistance to impact	2J (IK07) - Medium - (3)
Min. operating temperature	-5°C - (2)
Max. operating temperature	+60°C - (2)
Bending resistance	Pliable - Self-recovering - (2)
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

---

**Conduit properties**

Fire resistance: non-flame  
propagating

EN 61386.1, EN 61386.22

Compliant with Low Voltage  
Directive

LVD 2014/35/EU

Packed with 100% recyclable PE  
film

✓

