

50 MM PVC ICE -25 750N / R25



Very high resistance at low temperatures: -25°C. Made in PVC. Colour: grey (RAL 7037).

Art. code:	ICE50
xSpeed PVC ICE -25	50 mm
Classification	33412
Conduit colour	Grey - RAL 7037
External diameter	50 mm
Internal diameter	41,2 mm
Coil	25 m
Pallet	800 m

Technical information

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	No*
Liquid screed and concrete	Yes**
Chased wall - Plasterboard	Yes**
Chased floor	Yes**
False ceiling - Movable wall	Yes**
Prefab - Wood panels	Yes**
-	<i>*Check local regulations</i>
-	<i>**Only for electrical installations that do not require HF/LSFOH conducts systems</i>

Conduit technical specification

Material	PVC
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	2J (IK08) - Medium
Min. operating temperature	-25°C
Max. operating temperature	+60°C
Bending resistance	Pliable
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	
Standard	EN 61386.1, EN 61386.22, IK: EN 62262

Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

Conduit properties

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Packed with 100% recyclable PE

film



Related products



25 mm Speed F 750N / R100

Art. code: ICTA25F



50 mm Speed F 750N / R25

Art. code: ICTA50F



50 mm Speed F 750N / R50

Art. code: ICTA50F50



16 mm Speed 750N / R100

Art. code: ICTA16



50mm xSpeed HF UV R25

Art. code: ICTANUV5025RT8



40mm xSpeed HF UV R25

Art. code: ICTANUV4025RT20