

BEND CK HF 25 MM




The 90° tight bends CK IP67 of PM SMART line, are used for the connection of two rigid pipes. They are dust-tight and protected against the effects of temporary immersion in water, and they are also eco-friendly: Halogen Free according to European Standard EN 50642. Colour: grey (RAL 7035).

| | |
|---|------------------|
| Art. code: | CK25 |
| Colour | Grey - RAL 7035 |
| Diameter | 25 mm |
| Mini pack | 10 pcs |
| Maxi pack | 160 pcs |
| Compliant with Low Voltage Directive | LVD 2014/35/EU |
| Rigid | PM SMART Bend CK |

Technical information

Technical specification

| | |
|--|---|
| Material | Polycarbonate |
| Resistance to the penetration of solid objects | Dust-tight (6) |
| Resistance to water penetration | Protected against the effects of temporary immersion in water (7) |
| IP protection rating | IP67 |
| Fire resistance: non-flame propagating | ■ |
| HF - Halogen Free | EN 50642 |
| Standard | EN 61386.1, EN 61386.21, EN 60754-1, EN 60754-2, EN 60423, IEC 61034-2 |
| Compliant with Low Voltage Directive | LVD 2014/35/EU |
| Glow Wire Test (IEC EN 60695-2) | 850°C |
| Certifications |  |

