

COUPLING MK HF 25 MM





The tight couplings MK IP67 of PM SMART line, are used for the connection of two rigid pipes. They are dust-tight and protected against the effects of temporary immersion in water, and they are also eco-friendly: Halogen Free according to European Standard EN 50642. Colour: grey (RAL 7035).

Art. code:	MK25
Colour	Grey - RAL 7035
Diameter	25 mm
Mini pack	10 pcs
Maxi pack	160 pcs
Compliant with Low Voltage Directive	LVD 2014/35/EU
Rigid	PM SMART Coupling MK

Technical information

Technical specification

Material	Polycarbonate
Resistance to the penetration of solid objects	Dust-tight (6)
Resistance to water penetration	Protected against the effects of temporary immersion in water (7)
IP protection rating	IP67
Fire resistance: non-flame propagating	■
HF - Halogen Free	EN 50642
Standard	EN 61386.1, EN 61386.21, EN 60754-1, EN 60754-2, EN 60423, IEC 61034-2
Compliant with Low Voltage Directive	LVD 2014/35/EU
Glow Wire Test (IEC EN 60695-2)	850°C
Certifications	 

Related products



Coupling with clip 50 mm

Art. code: SML50



Cable drawer MON3 30 m

Art. code: MON330



Cable drawer MON 5 m

Art. code: MON5



HF Coupling 50 mm

Art. code: MFL50



Coupling with clip 25 mm

Art. code: SML25



Cable drawer MON3 25 m

Art. code: MON325