COUPLING PIPE-BOX BK HF 32MM



The tight couplings BK IP67 of PM SMART line, are used for the connection of rigid pipes with junction boxes. They are dust-tight and protected against the effects of temporary immersion in water, and they are also eco-friendly: Halogen Free according to European Standard EN 50642. Colour: grey (RAL 7035).

Art. code: BK32

Colour Grey - RAL 7035

Diameter 32 mm

Mini pack 10 pcs

Maxi pack 100 pcs

Compliant with Low Voltage

LVD 2014/35/EU Directive

Rigid PM SMART Coupling pipe-box BK

Pmflex:

Technical information

Technical	specification
. cciiiicai	Specification

Material Polycarbonate

Resistance to the penetration of

Dust-tight (6) solid objects

Protected against the effects of temporary immersion Resistance to water penetration

in water (7)

IP protection rating IP67

Fire resistance: non-flame

propagating
HF - Halogen Free EN 50642

EN 61386.1, EN 61386.21, EN 60754-1, EN 60754-2, EN Standard

60423, IEC 61034-2

Compliant with Low Voltage

LVD 2014/35/EU Directive

Glow Wire Test (IEC EN 60695-2) 850°C

Certifications (E®

Pmflex:

Related products







HF Coupling 50 mm

Art. code: MFL50

Coupling with clip 32 mm

Art. code: SML32

Coupling with clip 50 mm

Art. code: SML50







Cable drawer MON3 5 m

Art. code: MON35

HF Coupling 40 mm

Art. code: MFL40

GoEasy

Art. code: PMEASY