Pmflex

COUPLING PIPE-SPIREX RK HF 25MM



The tight couplings RK IP66 of PM SMART line, are used for the connection of rigid pipes with Spirex spiralled sheath 2311. They are dust-tight and protected against strong water jets, and they are also eco-friendly: Halogen Free according to European Standard EN 50642. Colour: grey (RAL 7035).

Art. code: RK25

Colour Grey - RAL 7035

Diameter 25 mm

Mini pack 10 pcs

Maxi pack 200 pcs

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Rigid PM SMART Coupling pipe-Spirex RK

Spirex PM SMART Coupling pipe-spirex RK

Technical information

Tack	nical	l cnacii	fication
I ECII	IIICa	ı specii	ication

Material Polycarbonate

Resistance to the penetration of Dust-tight (6)

solid objects

Protected against strong water jets (6)

IP protection rating IP66

Fire resistance: non-flame

Resistance to water penetration

propagating

EN 50642 HF - Halogen Free

EN 61386.1, EN 61386.21, EN 60754-1, EN 60754-2, EN Standard

LVD 2014/35/EU

60423, IEC 61034-2

Compliant with Low Voltage

Glow Wire Test (IEC EN 60695-2)

Directive

Certifications

850°C

Pmflex^{*}