FITTINGS SPIREX-BOX 20 MM



IP65 Fittings for Spirex 2311 and box connection. They are compliant with the European standards EN 61386.1 and EN 61386.23 and they are grey (RAL 7035). These articles are available also in black colour: the code changes, by replacing the final letter G with "N".

Art. code: RAG20G 3/4" - RAI25G 25x1,5 - RAP20PG21

Colour Grey - RAL 7035

Gas lead RAG20G 3/4"

Metric lead (IMQ) RAI25G 25x1,5

PG lead RAP20PG21

Diametro Spirex 20 mm

Pack 25 pcs

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Spirex Fittings Spirex-box

Pmflex:

Technical information

Technical specification

Material PVC

Resistance to the penetration of

solid objects

Dust-tight (6)

Resistance to water penetration Protected against water jets (5)

IP protection rating IP65

Fire resistance: non-flame

propagating

Standard

EN 61386.1, EN 61386.23, EN 60423

Glow Wire Test (IEC EN 60695-2) 850°C

Certifications



Pmflex:

Related products



Coupling with clip 25 mm

Art. code: SML25



GoEasy

Art. code: PMEASY



Cable drawer MON3 20 m

Art. code: MON320



Cable drawer MON 15 m

Art. code: MON15



HF Coupling 32 mm

Art. code: MFL32



Coupling with clip 16 mm

Art. code: SML16