FITTINGS SPIREX-BOX 25 MM



IP65 Fittings for Spirex 2311 and box connection. They are compliant with the European standards EN 61386.1 and EN 61386.23 and they are grey (RAL 7035). These articles are available also in black colour: the code changes, by replacing the final letter G with "N".

Art. code: RAG25G 1" - RAI32G 32x1,5 - RAP25PG29

Colour Grey - RAL 7035

Gas lead RAG25G 1"

Metric lead (IMQ) RAI32G 32x1,5

PG lead RAP25PG29

Diametro Spirex 25 mm

Pack 10 pcs

Compliant with Low Voltage

LVD 2014/35/EU

Directive

Spirex Fittings Spirex-box

Pmflex:

Technical information

Technical specification

Material PVC

Resistance to the penetration of

solid objects

Dust-tight (6)

Resistance to water penetration Protected against water jets (5)

IP protection rating IP65

Fire resistance: non-flame

propagating

Standard

EN 61386.1, EN 61386.23, EN 60423

Glow Wire Test (IEC EN 60695-2) 850°C

Certifications



Pmflex:

Related products







Coupling with clip 40 mm

Art. code: SML40

Cable drawer MON 5 m

Art. code: MON5

HF Coupling 32 mm

Art. code: MFL32







Coupling with clip 25 mm

Art. code: SML25

HF Coupling 20 mm

Art. code: MFL20

Cable drawer MON3 10 m

Art. code: MON310