

XRIGID HF 25 MM 750N



Medium class.

Ideal for exposed eco-compatible installations (interior walls and ceilings).

Ecological: Halogen Free according to European standard EN 50642.

Made in polyolefin.

Hot bendable for diameter 16, 20 and 25 mm with conduit bender.

Colour: grey (RAL 7035).

Art. code:	IRLHF25
xRigid HF 750N	25 mm
Classification	33431
Conduit colour	Grey - RAL 7035
External diameter	25 mm
Internal diameter	20,4 mm
Bar	3 m
Pack	60 m
Pallet	3240 m

Technical information

Environmental certificate


Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	Yes
Liquid screed and concrete	Yes*
Chased wall - Plasterboard	Yes
Chased floor	Yes
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes

 **To be used with IP67 connectors only (PM "Smart Line")*

Conduit technical specification

Material	Polyolefin
Compression resistance	750N (23°C, +/- 2°C) - Medium
Resistance to impact	2J (IK10) - Medium
Min. operating temperature	-25°C
Max. operating temperature	+105°C
Bending resistance	Rigid
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C
Certifications	
Standard	EN 61386.1, EN 61386.21, IK: EN 62262

Conduit properties

LS - Low Smoke	IEC 61034-2
----------------	-------------

Conduit properties

HF - Halogen Free

EN 50642

OH - Zero Halogen

IEC 60754-1; IEC 60754-2

Fire resistance: non-flame
propagating

EN 61386.1, EN 61386.22

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film



