

## XRIGID PVC 16 MM 320N



Light class. Ideal for exposed installations.  
Made in PVC.  
Colour: grey (RAL 7035).

---

<b>Art. code:</b>	IRS16
<b>xRigid PVC 320N</b>	16 mm
<b>Classification</b>	22211
<b>Conduit colour</b>	Grey - RAL 7035
<b>External diameter</b>	16 mm
<b>Internal diameter</b>	13 mm
<b>Pallet</b>	3060 m
<b>Bar</b>	3 m
<b>Pack</b>	102 m

## Technical information

---

### Environmental certificate

Environmental Product Declaration 




---

### Applications

Outdoor	No
Indoor	Yes
Exposed Installation	Yes*
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes
Chased floor	No
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes
-	<i>*Check local regulations</i>

---

### Conduit technical specification

Material	PVC
Compression resistance	320N (23°C, +/-2°C) - Light
Resistance to impact	1J - Light
Min. operating temperature	-5°C
Max. operating temperature	+60°C
Bending resistance	Rigid
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	  
Standard	EN 61386.1, EN 61386.21, IK: EN 62262

---

### Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

**Conduit properties**

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE  
film



