

PVC 25 MM 320N



Light class. Ideal for exposed installations.

Made in PVC.

Colour: grey (RAL 7035).

Art. code:	IRS25
Classification	22211
Conduit colour	Grey - RAL 7035
External diameter	25 mm
Internal diameter	21,7 mm
Pallet	1200 m
Bar	3 m
Pack	60 m
xRigid PVC 320N	25 mm

Technical information

Environmental certificate

Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	Yes*
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes
Chased floor	No
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes
-	<i>*Check local regulations</i>

Conduit technical specification

Material	PVC
Compression resistance	320N (23°C, +/-2°C) - Light
Resistance to impact	1J - Light
Min. operating temperature	-5°C
Max. operating temperature	+60°C
Bending resistance	Rigid
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	  
Standard	EN 61386.1, EN 61386.21, IK: EN 62262

Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

Conduit properties

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film



Related products



PP HF 20 mm 750N

Art. code: IRLHF20



PP HF 16 mm 750N

Art. code: IRLHF16



PP HF 16 mm 320N

Art. code: IRSHF16



PP HF UV 25 mm 750N

Art. code: IRLHFUV25



PVC 16 mm 320N

Art. code: IRS16



PP HF 50 mm 750N

Art. code: IRLHF50