

XRIGID PVC 40 MM 750N



Medium class. Ideal for all exposed installations (interior walls and ceilings).

Made in PVC.

Cold bendable for diameter 16, 20 and 25 mm with conduit bender.

Colour: grey (RAL 7035).

| | |
|--------------------------|-----------------|
| Art. code: | IRL40 |
| Classification | 33211 |
| Conduit colour | Grey - RAL 7035 |
| External diameter | 40 mm |
| Internal diameter | 36,2 mm |
| Pallet | 450 m |
| Bar | 3 m |
| Pack | 30 m |

Technical information

Environmental certificate

Environmental Product Declaration 

Environmental certificate

Environmental Product Declaration 

Applications

| | |
|------------------------------|------|
| Outdoor | No |
| Indoor | Yes |
| Exposed Installation | Yes |
| Liquid screed and concrete | Yes* |
| Chased wall - Plasterboard | Yes |
| Chased floor | Yes |
| False ceiling - Movable wall | Yes |
| Prefab - Wood panels | Yes |

**To be used with IP67 connectors only (PM "Smart Line")*

Conduit technical specification

| | |
|---------------------------------|-------------------------------|
| Material | PVC |
| Compression resistance | 750N (23°C, +/- 2°C) - Medium |
| Resistance to impact | 2J (IK07) - Medium |
| Min. operating temperature | -5°C |
| Max. operating temperature | +60°C |
| Bending resistance | Rigid |
| Insulation resistance | >100MΩ |
| Glow Wire Test (IEC EN 60695-2) | 960°C |

Certifications



Conduit technical specification

Standard EN 61386.1, EN 61386.21, IK: EN 62262

Conduit properties

Fire resistance: non-flame
propagating EN 61386.1, EN 61386.22

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film ■

