

XRIGID PVC 50 MM 320N



Light class. Ideal for exposed installations.

Made in PVC.

Colour: grey (RAL 7035).

Art. code:	IRS50
Classification	22211
Conduit colour	Grey - RAL 7035
External diameter	50 mm
Internal diameter	45,7 mm
Pallet	300 m
Bar	3 m
Pack	15 m

Technical information




Environmental certificate

Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	Yes*
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes
Chased floor	No
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes
-	<i>*Check local regulations</i>

Conduit technical specification

Material	PVC
Compression resistance	320N (23°C, +/-2°C) - Light
Resistance to impact	1J - Light
Min. operating temperature	-5°C
Max. operating temperature	+60°C
Bending resistance	Rigid
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	  
Standard	EN 61386.1, EN 61386.21, IK: EN 62262

Conduit properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

Conduit properties

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film



