

XRIGID PVC FB 16 MM 320N



Light class glass shaped rigid pipes made of PVC. They are ideal for eco-friendly exposed installations (internal walls and ceilings) and can also be cold-bent in diameters 16, 20, and 25 mm using MOPI bending springs.

Art. code:	IRS16FB
Classification	22211
Conduit colour	Grey - RAL 7035
External diameter	16 mm
Internal diameter	13 mm
Bar	3 m
Pack	75 m
Pallet	6600 m

Technical information

Environmental certificate

Environmental Product Declaration 

Applications

Outdoor	No
Indoor	Yes
Exposed Installation	Yes*
Liquid screed and concrete	No
Chased wall - Plasterboard	Yes
Chased floor	No
False ceiling - Movable wall	Yes
Prefab - Wood panels	Yes
-	<i>*Check local regulations</i>

Pipe technical specification

Material	PVC
Compression resistance	320N (23°C, +/-2°C) - Light - (2)
Resistance to impact	1J - Light - (2)
Min. operating temperature	-5°C - (2)
Max. operating temperature	+60°C - (1)
Bending resistance	Rigid - (1)
Insulation resistance	>100MΩ
Glow Wire Test (IEC EN 60695-2)	960°C (IMQ)
Certifications	  
Standard	EN 61386.1, EN 61386.21, IK: EN 62262

Pipe properties

Fire resistance: non-flame propagating	EN 61386.1, EN 61386.22
--	-------------------------

Pipe properties

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film



