

XRIGID PVC FB 20 MM 320N



Light class. Ideal for exposed installations.
Made in PVC. Glass shaped.
Colour: grey (RAL 7035).

| | |
|--------------------------|-----------------|
| Art. code: | IRS20FB |
| Classification | 22211 |
| Conduit colour | Grey - RAL 7035 |
| External diameter | 20 mm |
| Internal diameter | 17,1 mm |
| Bar | 3 m |
| Pack | 51 m |
| Pallet | 4488 m |
| xRigid PVC 320N | 20 mm |

Technical information




Environmental certificate

Environmental Product Declaration 

Applications

| | |
|------------------------------|---------------------------------|
| Outdoor | No |
| Indoor | Yes |
| Exposed Installation | Yes* |
| Liquid screed and concrete | No |
| Chased wall - Plasterboard | Yes |
| Chased floor | No |
| False ceiling - Movable wall | Yes |
| Prefab - Wood panels | Yes |
| - | <i>*Check local regulations</i> |

Conduit technical specification

| | |
|---------------------------------|---|
| Material | PVC |
| Compression resistance | 320N (23°C, +/-2°C) - Light |
| Resistance to impact | 1J - Light |
| Min. operating temperature | -5°C |
| Max. operating temperature | +60°C |
| Bending resistance | Rigid |
| Insulation resistance | >100MΩ |
| Glow Wire Test (IEC EN 60695-2) | 960°C (IMQ) |
| Certifications |    |
| Standard | EN 61386.1, EN 61386.21, IK: EN 62262 |

Conduit properties

| | |
|--|-------------------------|
| Fire resistance: non-flame propagating | EN 61386.1, EN 61386.22 |
|--|-------------------------|

Conduit properties

According to Low Voltage Directive LVD 2014/35/EU

Packed with 100% recyclable PE
film



