

UV COUPLING WITH CLIP 20 MM






Anti-UV couplings with clip for the connection of pliable conduits and rigid pipes. Thanks to the use of technologically advanced solutions, we present the range Pmflex Anti-UV, resistant to UV rays and atmospheric agents, suitable for outdoor installations and photovoltaic systems directly exposed to sunlight. Anti-UV products are made with specific materials and additives, tested in climate chamber with UV lamp, as specified by the norms CEI EN 50289 and CEI EN 50618 (former CEI 20-91). The chamber reproduces with intense UV light and with repeated rain and drying cycles the climatic conditions that the product will encounter outside. Pmflex Anti-UV products are also Halogen Free, in accordance with the European standard EN 50642.

Art. code:	SML20N
Colour	Black
Diameter	20 mm
Mini pack	50 pcs
Maxi pack	500 pcs
Compliant with Low Voltage Directive	LVD 2014/35/EU
Rigid	Anti-UV coupling with clip
Flex	Anti-UV coupling with clip

Technical information

Technical specification


Material	Polypropylene
Resistance to the penetration of solid objects	Protected against the ingress of solid objects with a diameter = / > 1.0 mm (4)
Resistance to water penetration	No protection (0)
IP protection rating	IP40
Fire resistance: non-flame propagating	■
LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1& IEC 60754-2
Standard	EN 61386.1, EN 61386.22
Glow Wire Test (IEC EN 60695-2)	750°C
Certifications	  

Related products




Cable drawer MON3 30 m

Art. code: MON330



HF Coupling 20 mm

Art. code: MFL20




HF Coupling 16 mm

Art. code: MFL16



Coupling with clip 32 mm

Art. code: SML32



HF Coupling 40 mm

Art. code: MFL40



Cable puller STCX 15 m

Art. code: STCX15