

## UV COUPLING WITH CLIP 50 MM



Anti-UV couplings with clip for the connection of pliable conduits and rigid pipes. Thanks to the use of technologically advanced solutions, we present the range Pmflex Anti-UV, resistant to UV rays and atmospheric agents, suitable for outdoor installations and photovoltaic systems directly exposed to sunlight. Anti-UV products are made with specific materials and additives, tested in climate chamber with UV lamp, as specified by the norms CEI EN 50289 and CEI EN 50618 (former CEI 20-91). The chamber reproduces with intense UV light and with repeated rain and drying cycles the climatic conditions that the product will encounter outside. Pmflex Anti-UV products are also Halogen Free, in accordance with the European standard EN 50642.

---

<b>Art. code:</b>	SML50N
<b>Colour</b>	Black
<b>Diameter</b>	50 mm
<b>Mini pack</b>	10 pcs
<b>Maxi pack</b>	90 pcs
<b>Compliant with Low Voltage Directive</b>	LVD 2014/35/EU
<b>Rigid</b>	Anti-UV coupling with clip
<b>Flex</b>	Anti-UV coupling with clip

## Technical information

---

### Technical specification

Material	Polypropylene
Resistance to the penetration of solid objects	Protected against the ingress of solid objects with a diameter = / > 1.0 mm (4)
Resistance to water penetration	No protection (0)
IP protection rating	IP40
Fire resistance: non-flame propagating	■
LS - Low Smoke	IEC 61034-2
OH - Zero Halogen	IEC 60754-1& IEC 60754-2
Standard	EN 61386.1, EN 61386.22
According to Low Voltage Directive	LVD 2014/35/EU
Glow Wire Test (IEC EN 60695-2)	750°C
Certifications	CE N S

## Related products



Cable drawer MON3 20 m

Art. code: MON320



Coupling with clip 20 mm

Art. code: SML20



GoEasy

Art. code: PMEASY



Coupling with clip 50 mm

Art. code: SML50



Cable drawer MON 10 m

Art. code: MON10



GoEasy Plus

Art. code: PMEASYPLUS